

## GWTT Bag Filter Units

GWTT, LLC offers a wide selection of Bag Filter Units for industrial and environmental applications. This product specification sheet is specific for our FT and FS series. The FT series represents our Filter Units which are staged on trailers for ease of maneuverability. The FS series represents our skid mounted units.

### Applications

- ◆ Environmental Remediation
- ◆ Oil and Gas
- ◆ Manufacturing
- ◆ Refinery
- ◆ Construction Dewatering

### Key Features

- ◆ Constructed with steel headers for rugged environments
- ◆ Duplex setup for continuous operation
- ◆ Contain a safety walkway for ease of filter change out
- ◆ Sample ports for compliance reporting
- ◆ FS Models equipped with fork pockets for ease of lifting
- ◆ FS Models equipped with 3 influent/effluent configurations

### Additional Services

- ◆ Bag filters ranging from 1-100 Micron
- ◆ Professionally trained treatment operators



**Model FS 800**



**Model FT 2300**



# Product Specifications

## Single Stage - Skid Mounted

Product Model #	FS800	FS 1000	FS 1200	FS 2300
Max Flow per Unit	800 GPM (19 BPM)	1000 GPM (23.8 BPM)	1200 GPM (28.6 BPM)	2300 GPM (54.7 BPM)
Footprint	4' x 4'	5' x 6'	6' x 7'	6' x 6'
No. of Bags per Unit	8	10	12	23
Skid or Trailer Mounted	Skid	Skid	Skid	Skid
Influent Hookup	6" or 8" Flange	6" Flange	8" Flange	12" Flange
Effluent Hookup	6" or 8" Flange	6" Flange	8" Flange	12" Flange

## Dual Stage - Skid Mounted

Product Model #	FS 400	FS 600	FS 800
Max Flow per Unit	400 GPM (9.5 BPM)	1000 GPM (23.8 BPM)	1200 GPM (28.6 BPM)
Footprint	6' x 6'	6' x 8'	8' x 10'
No. of Bags per Unit	4	6	8
Skid or Trailer Mounted	Skid	Skid	Skid
Influent Hookup	4" F Camlock	6" Flange	6" or 8" Flange
Effluent Hookup	4" M Camlock	6" Flange	6" or 8" Flange

## Dual Stage - Trailer Mounted

Product Model #	FT 400	FT 2300
Max Flow per Unit	400 GPM (9.5 BPM)	1000 GPM (23.8 BPM)
Footprint	6'7" x 11'6"	34' x 8' 6"
No. of Bags per Unit	4	23
Skid or Trailer Mounted	Trailer	Trailer
Influent Hookup	4" F Camlock	12" Flange
Effluent Hookup	4" M Camlock	12" Flange

In calendar year 2015, GWTT treated **14 Billion Gallons of Wastewater (333 Million Barrels or 26,600 Gallons Per Minute)** from hundreds of project sites in North America.

**“We Stand Ready to Execute”**



*Headquarters*

627 Mount Hope Road  
Wharton, NJ 07885  
800-770-0901  
973-983-0901

39 River Street  
Millbury, MA 01527  
800-962-4150  
508-755-7075

1204 East 12th Street—Bldg. 4C  
Wilmington, DE 19802  
877-654-0206  
302-654-0206

[www.gwttllc.com](http://www.gwttllc.com)